


CONVERTIBLE JET PUMPS

MODEL 3310P 1 HP
MODEL 3307P 3/4 HP
MODEL 3305P 1/2 HP

- Superior performance at depths to water of 100' or less
- Fiberglass reinforced thermoplastic pump housing for the highest corrosion resistance
- Ready to install heavy-duty dual-voltage motor preset at 230 volts for 3/4 and 1 HP models preset at 115 volts for 1/2 HP model
- Energy efficient motor
- Self-priming after pump housing is initially filled, check valve or foot valve required
- Pressure switch preset to 30-50 PSI



PERFORMANCE – Shallow Well of 25 Feet or Less

Model	HP	Warranty	Voltage	Amps	Pressure Switch		GPM Pumped at Different Depths to Water*					Pressure Shut-off
					On	Off	5'	10'	15'	20'	25'	
3310P	1	1-year	115/230	14.8/7.4	30	50	20.7	18.3	15.8	12.3	8.5	52 PSI
3307P	3/4	1-year	115/230	12.2/6.1	30	50	15.3	13.8	11.8	9.2	6.8	52 PSI
3305P	1/2	1-year	115/230	9.4/4.7	30	50	9.0	7.8	6.6	5.7	4.3	62 PSI

PERFORMANCE – Deep Well With 4" Diameter Casing or Larger

Model	GPM Pumped at Different Depths to Water*											Pressure Shut-off
	20'	25'	30'	40'	50'	60'	70'	80'	90'	100'	110'	
3310P	9	8.8	8.4	7.3	6.2	5	4.4	2.9	2	—	—	56 PSI
3307P	7.5	7.1	6.5	5.1	4	3	2.5	1.8	1.5	1	—	56 PSI
3305P	5.9	5.4	4.5	3.5	2.8	2.3	1.7	—	—	—	—	54 PSI

*All performances shown in gallons per minute at 40 PSI (pound per square inch) discharge pressure at top of well. FP4800 jet kit sold separately.

ORDERING INFORMATION

Model	UPC	Carton (L x W x H)	Cube	Pallet Qty.	Weight
3310P	0 22315 32428 2	21.063" x 12.313" x 12.375"	1.857	18	30.40 lbs.
3307P	0 22315 32427 5	21.063" x 12.313" x 12.375"	1.857	18	27.7 lbs.
3305P	0 22315 32426 8	21.063" x 12.313" x 12.375"	1.857	18	24.4 lbs.