

## Specifications

Engine .....	Honda GC160 (item# HBH13GC)/Honda GX160 (item# HBH13GX)/Honda GX270 (item# HBHXL13GX)
Engine Oil Type.....	Use Engine Manufacturer's Recommended Oil
Pump Capacity .....	7 GPM
Pump Displacement .....	7.4 cc
Pump Ports .....	1 /2"-14 O-Ring
Pump Rotation Direction .....	Counterclockwise
Hydraulic Fluid Type.....	AW32, ASLE H-150 or ISO 32
Hydraulic Tank Volume .....	5.6 gal (item# HBH13GC & HBH13GX)/10.3 gal (item# HBHXL13GX)
Hydraulic Tank Material.....	3/16" Steel
Hydraulic Tank Drain Port.....	1/2" NPT
Hydraulic Valve PSI Rating.....	900 PSI (item# HBH13GC & HBH13GX)/1500 PSI (item# HBHXL13GX)
Hydraulic Valve Type.....	One-Way Detent, One-Way Spring Return
Hydraulic Valve Inlet.....	3/4-14 NPT
Hydraulic Valve Outlet .....	3/4-14 NPT
Filter Type or replacement.....	Parker 12AT25CN25BBN or Hydra Buddy™ Part #787680
Quick Disconnect Fittings.....	ISO 7241-1 Series A