

# SEMI-TRASH PUMPS

## GASOLINE ENGINE SEMI-TRASH PUMPS

### Outstanding Features


- Powerful Honda and Koshin OHV engines with low oil sensors.
- Silicon carbide mechanical seals. Increased abrasive resistance, longer life, less maintenance.
- Impeller and volute manufactured from Spheroidal Graphite cast iron for longer life, less maintenance.
- Light weight die cast aluminum casing.
- Full roll cage protects pump and engine with vibration isolators.
- Strainer and wrench standard.



STV-80X



STH-50X




SEH-100T

### Specifications

	STH-50X	STV-50X	STH-80X	STV-80X	SEH-100T
<b>Suction Discharge Size</b>	2"NPT	2"NPT	3"NPT	3"NPT	4"NPT
<b>Maximum Capacity</b>	158 GPM	164 GPM	238 GPM	277 GPM	383GPM
<b>Maximum Head</b>	95'	82'	85'	82'	92'
<b>Maximum Suction Lift</b>	26'	26'	26'	26'	26'
<b>Maximum Pressure</b>	41.1 PSI	35.5 PSI	36.8 PSI	35.5 PSI	39.8 PSI
<b>Engine Type</b>	Honda GX120	KOSHIN K180	Honda GX160	KOSHIN K180	Honda GX240
<b>Displacement</b>	118 cc	180 cc	163 cc	180 cc	242 cc
<b>Horsepower</b>	3.5 HP	6.0 HP	4.8 HP	6.0 HP	7.1HP
<b>Fuel Tank Capacity</b>	0.86 Gal	0.95 Gal	0.95 Gal	0.95 Gal	1.58 Gal
<b>Continuous Operation Time Per Tank</b>	2.5 Hrs	2.0 Hrs	2.5 Hrs	1.6 Hrs	2.5 Hrs
<b>Fuel</b>	Unleaded Automotive Gasoline				
<b>Dimension (LxWxH)</b>	18"x14"x15"	16"x20"x17"	20"x15"x17"	21"x17"x19"	26"x26"x20"
<b>Dry Weight</b>	56 Lb	58 Lb	75 Lb	70 Lb	135 Lb

### Performance Curve



Note: Performance ratings are guaranteed minimum, not inflated maximum.