

Pump

YP20T



\$1,099 MSRP

TOP FEATURES:

1. The YP20T uses a 175cc, OHV 4-stroke engine that is quieter, more powerful, and consumes less fuel than comparable engines.
2. It has a powerful pump, pumping up to 184 gal/min (11,040 gal/hr) through a two-inch port.
3. Delivers a 92-foot total head, with a 26-foot suction head.
4. Can handle solids up to .79" (20 mm).
5. Durable Pump - Impeller and volute case are cast iron for greater strength and durability; and they withstand wear from grit, sand, silt, etc.
6. Outstanding Seal Durability - Newly adopted Japanese-made silicone carbide (SiC) seal - has better durability compared to conventional carbon ceramic seals.
7. 2-inch Standard National Pipe Thread (NPT) fittings connect easily with the suction and discharge hoses.
8. 3 year industrial and residential warranty with optional Y.E.S. for customer peace of mind.



Manufacturer's Suggested Retail Price (MSRP) shown. Does not include tax, title, prep or destination charges. Actual prices set by dealer.

FEATURES & BENEFITS

FEATURES:

DeWatering Applications - Use for these types of DeWatering applications: Job site excavations, Utility vaults, Motocross tracks, Mining sites, Lakes and ponds and Barge holds.

Powerful Pump - Pumps up to 184 gal/min (11,040 gal/hr). Use for moving massive amounts of water.

Cast iron cylinder lining has optimal heat dissipation — Cast iron cylinder lining has optimal heat dissipation.

Automatic oil warning system shuts off engine before oil level is low — Prevents engine damage, avoids costly repairs, minimizes down time, enhances long term durability.

Transistorized ignition provides lean, efficient spark — Maintenance-free and ensures fast, easy starting, reliable operation.

Auto-decompression — Automatically “opens” exhaust valve to reduce compression for easier starting.

EPA Emission Engine Life Rating — The YP20T meets the strictest environmental standards - EPA and CARB.

Tool and Strainer Kit - Standard equipment.

yamahamotorsports.com

For Accessories, visit yamahapartsandaccessories.com

SPECIFICATIONS:

Pump Type	Self-priming, Centrifugal
Suction Port	2 in
Discharge Port	2 in
Discharge Capacity	184 gal / min
Self Priming Time	100 sec / 26.25 ft
Total Head Lift	92 ft
Suction Head Lift	26 ft
Solids Handling (Max)	.79 in (20mm)
Engine	MZ 175 4-stroke,OHV, Forced air cooled
Fuel	Unleaded Gasoline
Fuel Capacity	4 gal
Starting Method	Recoil Starter
Dry Weight	105 lb
L x W x H	26.18 x 18.19 x 20.31 in
Limited Warranty	3 years