



Utility Pump Kit Model Shown

ALUMINUM SUBMERSIBLE UTILITY PUMPS

DEWALT UTILITY PUMPS are engineered to be contractor tough and deliver the performance you demand. Bring the pump that gets the job done.



DXWPUTILITY

GUARANTEED TOUGH®

SUBMERSIBLE UTILITY PUMP

1-1/2 IN. FPT DISCHARGE
Easy installation in new and existing applications.

THERMAL OVERLOAD PROTECTION
Prevents possible overheating and damage to motor.

HIGH FLOW IMPELLER
For maximum performance.

CARRY HANDLE
Easy to transport and install.

ROBUST MATERIALS
Engineered to be durable, high performance and reliable.

3/4 IN. GHT ADAPTER
For use with standard garden hose.



Multiple Applications

SPECIFICATIONS

MATERIAL	Aluminum
IMPELLER TYPE	Thermoplastic Impeller
SOLIDS HANDLING	Up to 3/8 in. Diameter
DISCHARGE SIZE	3/4 in. GHT or 1-1/2 in. FPT
RUNNING AMPS BY HP	4.8 - 8.3
CORD LENGTH	20 ft.
CORD LENGTH	120 Volt AC



Pump Dimensions

PERFORMANCE - GPM AT HEIGHT

Model	HP	0 ft.	5 ft.	10 ft.	15 ft.	20 ft.	25 ft.	30 ft.
DXWP61374	1/3	58	53	50	43	33	25	18
*DXWP61379	1/3	58	53	50	43	33	25	18
DXWP61774	3/4	83	77	73	65	55	45	33
*DXWP61779	3/4	83	77	73	65	55	45	33

PUMP INCLUDES

- (1) Submersible Utility Pump
- (1) 3/4 in. GHT x 1-1/2 in. MPT Adapter
- (1) *DXWP61379 and DXWP61779: 25 ft. of Industrial Hose and Camlock Fittings
- (1) Owners Manual

PUMP WARRANTY

10 YEAR
LIMITED WARRANTY

*HOSE KIT DXWP61379 AND DXWP61779



DEWALT®, GUARANTEED TOUGH® and the yellow/black color scheme are trademarks for DEWALT power tools, outdoor equipment, accessories, anchors and concrete adhesives and are used under license. Product may differ from that pictured. Does not affect function. Manufactured under license by: PEDROLLO GROUP INC. | 45 MARYLAND AVE EAST | ST. PAUL, MN 55117



DXWPUTILITY
Form 602500 Rev: 7/2022

GUARANTEED TOUGH.®

1-855-222-3841
customer.service@pedrollo-usa.com

www.DEWALT.com