

Cast Iron • Multi-Stage High Pressure Booster Pumps

Typical Application

When you need to boost your existing pressure by 50 to 130 PSI. Residential, commercial or agricultural high pressure washing.

Stainless Steel Motor Shaft

Includes heavy-duty ball bearings, on-board thermal overload protection and rated for continuous duty

Heavy-Duty Cast Iron Pump Adapter and Discharge

3/4" suction and discharge



1 HP 190 PSI
FP5732

3/4 HP 150 PSI
FP5722

1/2 HP 110 PSI
FP5712

PERFORMANCE												
MODEL/UPC	HP	MAX. PSI	VOLTS	GALLONS PER MINUTE					NPT PIPE SIZE		CARTON DIMS. (IN INCHES)	WT. (LBS.)
				50	70	90	110	130	SUCTION	DISCH.		
FP5732 022315165779	1	190	230/115	-	-	13	12	10.5	3/4"	3/4"	30.063 x 9.188 x 12.563 18/PALLET	48
FP5722 022315165762	3/4	150	230/115	-	13	10	8	-	3/4"	3/4"	30.063 x 9.188 x 12.563 18/PALLET	42.9
FP5712 022315165755	1/2	110	230/115	13	11	7	-	-	3/4"	3/4"	30.063 x 9.188 x 12.563 18/PALLET	38.9

Includes:

Detailed owner's manual