

Stainless Steel Shallow Well Jet Pumps

With Built-in Pressure Switch

Heavy-Duty Stainless Steel Construction

For the highest corrosion-resistance

Superior Performance

At depths to water of 25' or less

Heavy-Duty Dual-Voltage Motor

Preset at 230V

Self-Priming After Pump Housing Is Initially Filled

Check valve or foot valve required, sold separately



1 HP 17.5 GPM
FP4832

3/4 HP 11 GPM
FP4822

PERFORMANCE (GPM)							MAX PRESSURE SHUTOFF	VOLTAGE	PRESSURE SWITCH	
	DEPTH TO WATER	0'	5'	10'	15'	20'			25'	ON
FP4832	17.5	16.2	14.6	12.6	10.6	7.5	81 PSI	115/230	30	50
FP4822	11.0	11.0	11.0	11.0	9.0	7.2	64 PSI	115/230	30	50

• All performance shown in gallons per minute at 40 PSI discharge pressure

MODEL	WARRANTY	UPC	CARTON DIMENSIONS	PALLET QTY.	WEIGHT
FP4832	1 YEAR	022315160613	21.313" x 11.313" x 12.625"	18	33.75 LBS.
FP4822	1 YEAR	022315160606	21.313" x 11.313" x 12.625"	18	29.05 LBS.

Includes:

Factory-installed 30/50 preset pressure switch, detailed owner's manual

