

# 554650 – VCMA-20ULST-PRO

Our VCMA-20-PRO Series effectively delivers high-efficiency condensate removal from air conditioners, gas furnaces, and condensing boilers.

Item: 554650

Model: VCMA-20ULST-PRO

## Ratings

HP	1/30 hp
Frequency	60 Hz
Amps - Full Load	1.5 A
Full Load Watts	93 W
Volts	115 VAC
Cord Length	6 ft
Maximum Flow Rate - 60Hz	1.4 gpm / 84 gph
Flow Rate At 1ft	1.4 gpm / 84 gph
Max PSIG	9.1 PSI
Max Flow Rate - 50Hz	1.4 gpm / 84 gph
Shut-Off	21 ft
Safety Switch	Yes

## Liquid

Max Fluid Temperature	140 °F
-----------------------	--------

## Materials of Construction

Pump Base Material	Plastic
Pump Body Material	Plastic
Check Valve	Yes

## Installation

Discharge Thread	Barb
Discharge Type	Barb
Discharge	0.38 "
Product Length	10.2 "
Product Width	4.8 "
Product Height	6.5 "
Product Weight	5.5 lb
Product Weight w/ Pack	6 lb
Carton Length	12 "
Carton Width	7 "
Carton Height	6.81 "
Tubing Included	Yes

## Other

Accessories / Repair Kits	Tank 154390_x000D_ Rubber Feet 925047_x000D_ Check Valve 3/8" 154724_x000D_ Tank Bracket 154483_x000D_ T-20/25 One carton of 25 pieces of 20' (6.01m) length 3/8" (9.5 mm) ID VC tubing 599033_x000D_ T-3/8 100' (640.1 m) of 3/8" (9.5 mm) ID x1/2" (12.37 mm) OD clear tubing 599107_x000D_ CV-X38 3/8" (9.5 mm) OD rigid plastic or copper tubing 599058_x000D_ Anti-Sweat Sleeve 10000014026_x000D_ Check Valve 1/4" OD 154725
Electrical Agency Approvals	CSA/UL
Standard Warranty	36 Months
	<a href="#">Warranty Terms and Conditions Link</a>