

## SPECIFICATIONS

Model	HP	Amps	Intake	Discharge	Pressure Gauge Port	Suction Lift	Discharge Pressure (PSI)					Max. Pressure PSI	Max. Head	Max. Flow GPM
							20	30	40	50	60			
							US Gallons Per Minute							
LG-SWJ50	1/2	8.4 A @ 115 V 4.2 A @ 230 V	1-1/4" FIP	1" FIP	1/8" NPT	5'	13.6	12.6	7.3	3.4	1	64	148'	12
						15'	9.7	9.5	5.5	2.8	0.3	60	139'	
						25'	4.7	5	4.1	1.7	0	57	133'	
LG-SWJ75	3/4	9.0 A @ 115 V 4.5 A @ 230 V	1-1/4" FIP	1" FIP	1/8" NPT	5'	13.4	13	9.1	4.8	1.5	70	161'	13
						15'	9.8	9.7	7.2	3.4	0.8	66	152'	
						25'	4.4	5.2	4.8	1.8	0.4	62	144'	
LG-SWJ75/ LG14H	3/4	9.0 A @ 115 V 4.5 A @ 230 V	1-1/4" FIP	1" FIP	1/8" NPT	5'	13.4	13	9.1	4.8	1.5	70	161'	13
						15'	9.8	9.7	7.2	3.4	0.8	66	152'	
						25'	4.4	5.2	4.8	1.8	0.4	62	144'	


# CLEANWATER PRODUCTS

## SHALLOW WELL JET PUMPS

## INSTALLATIONS

### LG-SWJ75/LG14H

Prepackaged Pump/Tank System



### LG-SWJ75

### LG-SWJ50

Tank Sold Separately



**Need service or support? We're here to help.**  
PRODUCT SELECTION | INSTALLATION | MAINTENANCE



**TECHNICAL SERVICE LINE**  
888.956.0000

Form 996917 Rev. 001 02/18



**TECHNICAL SERVICE LINE**  
888.956.0000

## 3/4 HP SHALLOW WELL JET PUMP/TANK SYSTEM



**LG-SWJ75/LG14H** | 97080707

- Includes all features of the 3/4 HP Shallow Well Jet Pump
- Jet pump and pre-charged pressure tank are factory assembled and ready to install
- Pre-charged steel tank has high grade butyl diaphragm water chamber - 13.2 U.S. gallons
- Low profile, compact horizontal pressure tank

## 3/4 HP SHALLOW WELL JET PUMP



**LG-SWJ75** | 97080706

- Ideal for the supply of fresh water to rural homes, farms, and cabins that have suction lifts down to 25'
- Includes factory pre-set 30/50 pressure switch
- Heavy-duty cast iron construction
- Dual voltage motor, 115/230 Volts
- 1-1/4" FIP suction and 1" discharge
- Max flow of 13 GPM
- 70 PSI
- 9.1 GPM at 40 PSI and 5' lift

## 1/2 HP SHALLOW WELL JET PUMP



**LG-SWJ50** | 97080504

- Ideal for the supply of fresh water to rural homes, farms, and cabins that have suction lifts down to 25'
- Includes factory pre-set 30/50 pressure switch
- Heavy-duty cast iron construction
- Dual voltage motor, 115/230 Volts
- 1-1/4" FIP suction and 1" discharge
- Max flow of 12 GPM
- 64 PSI
- 7.3 GPM at 40 PSI and 5' lift