

PROLINE HY-DRIVE WATER PUMPS WITH PROTECTIVE CAGE

PROLINE HY-DRIVE PUMPS are unique, high-capacity pumps designed specifically for use in larger pond installations. The Hy-Drive design combines the benefits of magnetic and direct drive technologies to deliver great performance and high efficiency in an extremely quiet, low maintenance package. The heavy-duty polypropylene enclosure has a built-in carry handle and effective molded-in debris screen. Hy-Drive pumps can be positioned vertically or horizontally and can be used as a submersible pump or as an in-line, external pumping source. Available in 1600, 2100, 2600, 3200, 4000, 4800, and 6000 GPH capacities.

FEATURES

- Powerful, Efficient Hybrid Magnetic Induction Motor
- High-Efficiency Vortex Impeller
- Whisper Quiet Continuous Duty Operation
- Oil-Free / Fish Safe
- Convenient Carry Handle
- Submersible or In-line Operation
- Threaded Female Couplings and Fittings Included
- Extra-Long Clog Resistant Filter Screen
- Can be positioned vertically or horizontally
- 20' Grounded Power Cord
- Packed 2 per Master Carton
- 3 Year Limited Warranty

1600 HY-DRIVE - ITEM# 02663

Max. Watts/Amps	120/1.0
Inlet	1"
Outlet	1"
Cord Length	20'
Dimensions (L x W x H)	13" x 6 3/8" x 6"

2100 HY-DRIVE - ITEM# 02665

Max. Watts/Amps	190/1.5
Inlet	1"
Outlet	1"
Cord Length	20'
Dimensions (L x W x H)	13" x 6 3/8" x 6"

2600 HY-DRIVE - ITEM# 02667

Max. Watts/Amps	270/2.2
Inlet	1"
Outlet	1"
Cord Length	20'
Dimensions (L x W x H)	15" x 7.25" x 7.75"

3200 HY-DRIVE - ITEM# 02680

Max. Watts/Amps	160/1.5
Inlet	1 1/2"
Outlet	1 1/2"
Cord Length	20'
Dimensions (L x W x H)	15" x 7.25" x 7.75"



ProLine Hy-Drive inside of Pump Bag (sold separately)



6000 ProLine Hy-Drive without Pump Housing



316 STAINLESS STEEL ROTOR FOR GREATER CORROSION & WEAR RESISTANCE

PM NAME	PM ITEM#	Watts	Flow at 1'	Flow at 3'	Flow at 5'	Flow at 7'	Flow at 10'	Flow at 15'	Flow at 20'	Flow at 25'	Shut-Off (Feet)
PLHD 1600	02663	120	1700	1575	1400	1250	1000	375	-	-	17'
PLHD 2100	02665	190	2075	1900	1750	1600	1300	850	300	-	22' 5"
PLHD 2600	02667	270	2550	2525	2450	2225	1975	1625	1250	300	26' 5"
PLHD 3200	02680	160	3300	2700	2050	1650	650	-	-	-	12'
PLHD 4000	02675	200	4000	3300	2700	2350	1475	-	-	-	13'
PLHD 4800	02670	280	5000	4500	3900	3150	2350	800	-	-	18' 5"
PLHD 6000	02683	675	5500	5100	4700	4200	3650	2450	1150	-	22' 5"

PROLINE SKIMMER PUMPS WITH HY-DRIVE TECHNOLOGY



PROLINE HY-DRIVE SKIMMER PUMPS are designed to fit most pond skimmer filters while delivering reliable and powerful performance. Employs hybrid technology that integrates the power of direct drive pumps and the energy efficiency and safety of magnetic drive pumps. Continuous duty pumps move large volumes of water silently and efficiently through filtration systems or to a waterfall, stream or fountain. High efficiency vortex impeller, ceramic impeller shaft and bearings provide energy savings while maintaining high output.

FEATURES

- Designed to Move Large Volumes of Water, Silently and Efficiently
- High Efficiency Vortex Impeller
- Unique Upright Design, Specifically for Pond Skimmer Use
- Rigid Pre-Filter Stabilizes Pump while Protecting it from Large Debris
- 1 1/2" Male Outlet and 1 1/2" Elbow Included
- Pump Bag Included for Extra Pump Protection
- Packed 2 per Master Carton
- 3 Year Limited Warranty

1400 GPH SKIMMER PUMP - ITEM# 20350

Max. Flow Rate	1400 GPH
Max. Pumping Height	19'
Max. Watts/Amps	150/1.3 A
Cord Length	20'

2550 GPH SKIMMER PUMP - ITEM# 20355

Max. Flow Rate	2550 GPH
Max. Pumping Height	11' 5"
Max. Watts/Amps	147/1.3 A
Cord Length	20'

5100 GPH SKIMMER PUMP - ITEM# 20360

Max. Flow Rate	5100 GPH
Max. Pumping Height	30'
Max. Watts/Amps	439/3.6 A
Cord Length	20'

6600 GPH SKIMMER PUMP - ITEM# 20365

Max. Flow Rate	6600 GPH
Max. Pumping Height	30' 6"
Max. Watts/Amps	593/4.9 A
Cord Length	20'



PM NAME	PM ITEM#	Watts	Flow at 1'	Flow at 3'	Flow at 5'	Flow at 7'	Flow at 10'	Flow at 15'	Flow at 20'	Flow at 25'	Flow at 30'	Shut-Off (Feet)
SKP 1400	20350	150	1350	1250	1150	1100	925	650	-	-	-	19'
SKP 2550	20355	147	2375	2000	1500	1050	450	-	-	-	-	11' 6"
SKP 5100	20360	439	5100	5050	4650	4375	3900	3050	2375	1675	-	30'
SKP 6600	20365	593	6600	6275	5500	4925	4325	3325	2425	1850	550	30' 6"