





SHALLOW WELL JET PUMP

Superior Pump • 2301 Traffic St. NE • Minneapolis, MN 55413 USA • 800-495-9278 • www.superiorpump.com

3/4_{HP} SHALLOW WELL JET PUMP

- 3/4 HP dual voltage motor (115/230v -7.8/3.9 amps)
- Built-in thermal overload protection for safety
- Rugged cast iron pump body for durability
- Tough thermoplastic impeller
- Glass filled thermoplastic diffuser
- Cast iron seal plate
- Pre-mounted, fully adjustable pressure switch
- For shallow well application up to 25' depth
- Maximum pressure: 74 psi
- Pressure switch pre-set to 20/40 PSI
- 1-1/4" NPT suction
- 1" NPT discharge



PERFORMANCES

Approximate gallon per minute output at 40 psi							Maximum Pressure
Lift	0'	5'	10'	15'	20'	25'	
GPM	11.8	11.3	10.8	10.2	9.3	8.3	74 psi

TECHNICAL SPECIFICATIONS

Model	HP	Amps	Suction Size	Discharge/ Drive Port Size	Pressure Switch	Max Pressure	Max Flow Rate	Warranty
94705	3/4	7.8/3.9	1-1/4"	1"	20/40	74 psi	13.75 GPM	3 Year

